

6 Ports 10/100/1000M Industrial Fiber POE Switch with 4x RJ45 and 2x GE SFP

LIP0X6-2SFP is a 4x 10/100/1000M POE RJ45 port and 2x SFP port Industrial POE switch. Its casing is IP40 rated and meet EMC industrial level 4 requirements. Features 3KV network port surge protection which is important for harsh outdoor environment and ensure the reliability of the uninterrupted system.



FEATURES

- 4x 10/100/1000M RJ45 POE and 2x GE SFP
- Supports IEEE 802.3x flow control for Full-duplex Mode and backpressure for Half-duplex Mode
- Supports IEEE 802.3af (15.4W per port) and 802.3at (30W per port)
- RJ45 Ports AUTO Negotiation/AUTO MDI/MDIX
- Storage Exchange Forwarding Mechanism and 4M Forward Memory
- Standard IU rack mount/Desktop design
- Supports Wire-Speed forwarding

SPECIFICATIONS

6 Ports 10/100/1000M Industrial Fiber POE Switch with 4x RJ45 and 2x GE SFP	
Number of POE ports (10/100/1000BaseT)	4
Number of GE SFP port	2
Power Pin Assignment	1/2and 3/6 , or alternatively over 4/5(+) and 7/8 (-)
Performance Specifications	
Transmission Method	Store-And-Forward
Network Protocol and Standards	IEEE 802.3u
	IEEE 802.3x Flow Control
POE standard	IEEE802.3af or IEEE802.3at
POE power	15.4W per POE port (IEEE802.3af)
	30W per POE port (IEEE802.3at)
Enviornmental	
Operating temperature	40 ~ 80°C
Storage temperature	-40 ~ 85°C
Operating humidity	5 ~ 95% non condensation
Power Supply	DC 48-57V
Power Consumption	Standby:<4W;Full load:<60W
LED indicators	Power supply, network status, POE status
Physical	
Dimension	120 x 100 x 30mm
Weight	0.7kg

FUNCTIONAL DIAGRAM



ORDERING INFORMATION

PN	DESCRIPTION
LIPOX6-2SFP-x	6 Ports 10/100/1000M Industrial Fiber POE Switch with 4x RJ45 and 2x GE SFP
x-	F- IEEE802.3af (154W per port)
	T- IEEE802.3at (30W per port)
PEA-52-65	Power Adaptor 220VAC~52VDC @ 65W
PEA-52-110	Power Adaptor 220VAC~52VDC @ 110W